

Outdoor Directional Panel Antenna

ODP-065R18BV

XPol, 806-960MHz, 65°, 17.6dBi

Comba

Technical Specifications

Electrical

Frequency Range	MHz	806-896	870-960
Polarization		± 45	
Gain	dBi	17.1	17.6
Horizontal Beamwidth	deg	65	
Vertical Beamwidth	deg	7	
Electrical Downtilt Range	deg	0-7	
First Upper Sidelobe Suppression	dB	> 18	
Front-To-Back Ratio	dB	> 25	
VSWR		$\leq 1.5:1$	
Isolation Between Ports	dB	> 30	
Cross-polar Discrimination @ 0°	dB	> 20	
3rd Order Intermodulation @ 2x43 dBm	dBc	< -150	
Maximum Power per Port	W	250	
Impedance	Ω	50	
Lightning Protection		Direct Ground	






Mechanical




Dimensions, HxWxD	mm (in)	2615x265x141 (103.0x10.4x5.6)
Weight, without Mounting Kit	kg (lb)	26.0 (57.3)
Weight, with Mounting Kit	kg (lb)	31.5 (69.4)
Radome Material and Color		Fiberglass, Light Grey, RAL7035
Mounting Kit		00-Z110(08)
Reflector Material		Zinc
Radiating Element Material		Zinc Composite
Connector Type and Location		2 x 7/16 DIN-Female, Bottom
Operational Temperature	°C	-55 to +70
Operational Humidity	%	≤ 95
Operational Wind Speed	km/h (mph)	200 (124.3)
Shipping Dimensions, HxWxD	mm (in)	2915x375x280 (114.6x14.7x11.0)
Shipping Weight	kg (lb)	38.0 (83.8)

Antenna Pattern

Vertical pattern



Horizontal pattern



806MHz @ 0°

870MHz @ 0°

960MHz @ 0°