

Outdoor Directional Panel Antenna

ODP-065V15Bxx

VPol, 824-960MHz, 65°, 16.0dBi

Comba

Technical Specifications

Electrical

Frequency Range	MHz	806-896	870-960
Polarization		Vertical	
Gain	dBi	15.0	16.0
Horizontal Beamwidth	deg	65	
Vertical Beamwidth	deg	14	
Electrical Downtilt – Fixed (Options)	deg	0, 2, 4, 6	
First Upper Sidelobe Suppression	dB	> 18	
Front-To-Back Ratio	dB	> 28	
VSWR		≤ 1.35:1	
3rd Order Intermodulation @ 2x43 dBm	dBc	< -150	
Maximum Power	W	200	
Impedance	Ω	50	
Lightning Protection		Direct Ground	






Mechanical




Dimensions, HxWxD	mm (in)	1315x280x124 (51.7x11.0x4.9)
Weight, without Mounting Kit	kg (lb)	16.5 (36.4)
Weight, with Mounting Kit	kg (lb)	18.8 (41.4)
Radome Material and Color		Fiberglass, Light Grey, RAL7035
Mounting Kit		SJA-B-12(16)
Reflector Material		Aluminum
Radiating Element Material		Zinc Composite
Connector Type and Location		7/16 DIN-Female, Bottom
Operational Temperature	°C	-55 to +70
Operational Humidity	%	≤ 95
Operational Wind Speed	km/h (mph)	200 (124.3)
Shipping Dimensions, HxWxD	mm (in)	1595x335x230(62.7x13.2x9.0)
Shipping Weight	kg (lb)	22.3 (49.2)

Antenna Pattern

Vertical pattern



Horizontal pattern



824MHz @ 0°

890MHz @ 0°

960MHz @ 0°