

Outdoor Directional Panel Antenna

ODV-065R18K

XPol, 1710-2170MHz, 65°, 18.0dBi

Comba

Technical Specifications

Electrical

Frequency Range	MHz	1710-1880	1850-1990	1920-2170
Polarization			± 45	
Gain	dBi	17.6	17.8	18.0
Horizontal Beamwidth	deg		65	
Vertical Beamwidth	deg		6.5	
Electrical Downtilt Range	deg		0-8	
First Upper Sidelobe Suppression	dB		> 18	
Null Fill	dB		< 22	
Front-To-Back Ratio	dB		> 28	
VSWR			≤ 1.5:1	
Isolation Between Ports	dB		> 30	
Cross-polar Discrimination @ 0°	dB		> 18	
3rd Order Intermodulation @ 2x43 dBm	dBc		< -150	
Maximum Power per Port	W		100	
Impedance	Ω		50	
Lightning Protection			Direct Ground	




Mechanical


Dimensions, HxWxD	mm (in)	1315x173x81 (51.8x6.8x3.2)
Weight, without Mounting Kit	kg (lb)	10.5 (23.1)
Weight, with Mounting Kit	kg (lb)	14.0 (30.9)
Radome Material and Color		Fiberglass, Light Grey, RAL7035
Mounting Kit		SJA-B-14C(10)
Reflector Material		Aluminum
Radiating Element Material		Zinc Composite
Connector Type and Location		2 x 7/16 DIN-Female, Bottom
Operational Temperature	°C	-55 to +70
Operational Humidity	%	≤ 95
Operational Wind Speed	km/h (mph)	200 (124.3)
Shipping Dimensions, HxWxD	mm (in)	1460x250x160 (57.5x9.8x6.3)
Shipping Weight	kg (lb)	16 (35.3)

Antenna Pattern


Vertical pattern




Horizontal pattern



1710MHz @ 0°



1920MHz @ 0°



2170MHz @ 0°