

Outdoor Directional Twin Antenna

ODV-065R18K18K0202 XXPol, 1710-2170/1710-2170MHz, 65°, 18.3/18.3dBi

Comba

Technical Specifications

Electrical

Frequency Range	MHz	1710-1880	1850-1990	1920-2170
Polarization		± 45		
Gain	dBi	17.7	18.0	18.3
Horizontal Beamwidth	deg	65		63
Vertical Beamwidth	deg	6.0		
Electrical Downtilt Range	deg	2-10 / 2-10		
First Upper Sidelobe Suppression	dB	> 15		
Front-To-Back Ratio	dB	> 26		
VSWR		≤ 1.5:1		
Isolation Between Ports	dB	> 28		
Cross-polar Discrimination @ 0°	dB	> 16		
3rd Order Intermodulation @ 2x43 dBm	dBc	< -150		
Maximum Power Per Port	W	100		
Impedance	Ω	50		
Lightning Protection		Direct Ground		






Mechanical




Dimensions, HxWxD	mm (in)	1350x320x110 (53.1x12.6x4.3)
Weight, without Mounting Kit	kg (lb)	24.5 (54.0)
Weight, with Mounting Kit	kg (lb)	29.5 (65.0)
Radome Material and Color		Fiberglass, Light Grey
Mounting Kit		SJA-B-12R(17)
Reflector Material		Aluminum
Radiating Element Material		Zinc Composite
Connector Type and Location		4 x 7/16 DIN-Female, Bottom
Operational Temperature	°C	-55 to +70
Operational Humidity	%	≤ 95
Operational Wind Speed	km/h (mph)	200 (124.3)
Shipping Dimensions, HxWxD	mm (in)	1675x395x200 (65.9x15.5x7.9)
Shipping Weight	kg (lb)	34.5 (76.0)

Antenna Pattern

Vertical pattern



Horizontal pattern



1870MHz @ 2°

1980MHz @ 2°

2170MHz @ 2°